

### FRAUNHOFER INSTITUTE FOR PHOTONIC MICROSYSTEMS IPMS



- 1 MEMS scanner module LAMDA (scan head) with segmented receiving scanner (left) and emission scanner (right).
- 2 Large aperture MEMS scanning devices mounted flex on glass.

## Fraunhofer Institute for Photonic Microsystems IPMS

Maria-Reiche-Str. 2 01109 Dresden

#### Contact

Dr. Michael Scholles Phone +49 351 8823-201 michael.scholles@ipms.fraunhofer.de

Dr. Thilo Sandner Phone +49 351 8823-152 thilo.sandner@ipms.fraunhofer.de

www.ipms.fraunhofer.de

# LAMDA – LARGE APERTURE MEMS SCANNER MODULE FOR 3D DISTANCE MEASUREMENT

Traditional laser scanners for 3D distance measurement involve expensive, heavy and large rotating or vibrating mirrors as a means for light deflection of the scanning TOF (time of flight) distance measurement. Typically, the precision of TOF distance measurements is limited by the amount of signal light available at the detector. Hence, a scanning mirror with large aperture is required for LIDAR systems to collect small amounts of light reflected or scattered by the measured target. Its replacement by a micromechanical scanning mirror device is not straightforward, since a large mirror aperture of the receiver optics must be guaranteed in addition to sufficiently large optical scan angles (>40°) and high scan frequency of more then 100 Hz. Contrary, the aperture of a single MEMS scanning mirror is limited to small values of typically 1...4 mm diameter due to the dynamic mirror deformation.

The Fraunhofer IPMS has developed so far highly miniaturized MEMS scanner devices enabling significant large deflection amplitudes (up to ±35°, mechanical) and low power consumption in electrostatic resonant operation, very promising for miniaturized and portable applications. Customized 1D/2D scanner devices are fabricated from single crystalline silicon in a qualified fully CMOS compatible MEMS process suitable for mass fabrication resulting in highly robust and reliable MEMS devices that withstand easily a shock of 2500 g.

Now the Fraunhofer IPMS presents for the first time the prototype of a new large aperture 1D MEMS scanner module especially designed for phase-based laser radar systems. The Lamda module is constructed based on a novel segmented MEMS scanner device consisting of identical scanning mirror elements realized using the flexible MEMS technology of Fraunhofer IPMS. Therefore, Fraunhofer IPMS has designed a scalable MEMS scanner device composed of identical silicon mirror elements each having a comparatively large aperture of 2.51 x 9.51 mm<sup>2</sup> and a large optical scan range of ±30°. The 1D MEMS scanner module comprises two separate scanning channels: (a) a single scanning mirror of the collimated transmitted beam oscillates parallel to (b) a segmented scanning mirror device of the receiver optics. Light paths of emitting and receiving optics are optically separated to avoid any crosstalk in the final LIDAR system essential for phase-based TOF measurements . The receiver optics use a configuration of 2 x 7 identical mirror elements resulting in a total aperture of 334 mm<sup>2</sup> and filling factor of 80%. All mirrors are driven electro-statically resonant at 250 Hz by means of separate in-plane comb drives with an identical frequency close to the mechanical resonance for oscillation around their long symmetry axes. Thus, the transmitted beam is sent via a separate emitting master mirror of the same mechanical dimensions as one single element of the segmented receiving mirror. Since laser energy is emitted in only one direction, all the receiving mirrors are synchronized to the master scanner by

the driving control electronics to point in the same direction. Hence, the effective apertures of the receiving mirrors add up to form a sufficiently large aperture if all receiving mirrors are synchronized in phase to the emitting master mirror in order to maximize the optical signal of the detector system. To realize the mirror synchronization, miniaturized position sensors are integrated into the Lamda module for each individual mirror element. Thus, a precise control of the mirror motion is achieved so that all receiving mirror elements can be slaved to the motion of the emission mirror. The Lamda scanner module has a total size of about 40 x 52 x 45 mm<sup>3</sup> and provides a synchronous position signal of the actual scan angle required for the final 3D laser radar system.

The segmented MEMS scanning device satisfies at the same time the demand of a comparatively large optically active area, 2.51 x 9.51 mm<sup>2</sup> per single mirror element, while keeping the resonance frequency of 250 Hz at a value that matches well to current TOF laser distance measurement systems with point measurement rates of typical 250 - 1000 kHz. Thus, the optical scan range of ±30 degrees is split into 500 - 2000 intervals. The new concept of using a segmented MEMS device consisting of identical synchronized MEMS scanner elements permits large reception apertures for LIDAR systems while preserving the outstanding reliability, high scanning speed, compact size and small system weight that can be expected from MEMS. In comparison to systems with conventional scanner components, the new 1D MEMS scanner module enables 3D LIDAR systems to become significantly smaller and more robust, higher scan rates can be realized without additional efforts (e.g. air bearings). Hence, the Lamda module is very promising for many applications e.g. in security, machine vision and even for portable outdoor use.

#### System parameters of MEMS scanner module

Parameter	Min	Тур.	Max	Unit
Scan head form factor (w/o flex connectors)		40 x 52 x 45		mm³
Electronics form factor		80 x 55 x 27		mm <sup>3</sup>
Optical interface	Window, I	broadband AR coating (VIS)	, 1.5° tiltec	1
Scanner frequency		250		Hz
Deflection angle (mechanical)	±9.7		±15	0
Optical field of view	39		60	0
Sending / Single scanner aperture		2.51 x 9.51		mm²
Receiver scanner total aperture		334		mm²
Optical fill factor receiver scanner		80		%
Interfaces	Display, U	SB, hardware interface (SPI	+ proprieta	iry I/O)
Supply voltage		12		V
Power consumption		2.2		W